



SAFETY DATA SHEET

METHYLATED SPIRITS

OMIKRON AUTO DETAILING PRODUCTS

Product code **METH**

Version No: **1.0**

Issue date: **01/09/2025**

Safety Data Sheet according to WHS and ADG requirements

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	METHYLATED SPIRITS
Product code	METH
Pack sizes	5L/ 20L
Proper shipping name	ETHANOL (ETHYL ALCOHOL)

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Cleaning solvent
--------------------------	------------------

Details of the manufacturer/importer

Registered company name	OMIKRON AUTO DETAILING PRODUCTS
Address	12 McPherson Rd, Smeaton Grange, NSW, 2567
Telephone	(02) 9824 5966
Website	www.omikron.com.au
Email	sales@omikron.com.au

Emergency telephone number

Association / Organisation	Poisons Information Centre
Emergency telephone numbers	13 1126
Other emergency telephone numbers	Not available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the Model WHS Regulations and the ADG Code.

Poisons Schedule	5
GHS Classification	Flammable Liquid Category 2, Eye Damage/ Irritation Category 2
	<i>Classification drawn from HCIS and ECHA C&L Inventory.</i>

Label elements

Hazard pictograms	
-------------------	---

SIGNAL WORD	DANGER
-------------	---------------

Hazard statement(s)

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation

Precautionary statement(s) Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking .
P233	Keep container tightly closed.
P240	Ground/Bond container and receiving equipment.
P241	Use explosion-proof electrical / ventilating / lighting / intrinsically safe equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist /vapours/spray
P280	Wear protective gloves/eye protection.

Precautionary statement(s) Response

P305+P351+P338+P310	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTRE or doctor
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
-----------	--

Precautionary statement(s) Disposal

P501	Dispose of contents / container in accordance with local government regulations.
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64-17-5	100	<u>Ethanol</u>

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical advice/attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of rash or irritation.
Inhalation	If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. If patient is having difficulty breathing seek medical advice / attention.
Ingestion	If swallowed do NOT induce vomiting. Immediately seek medical advice / attention. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Extinguishing media	Foam. Dry chemical powder. BCF (where regulations permit). Carbon dioxide. Water spray or fog - Large fires only.
---------------------	---

Special hazards arising from the substrate or mixture.

Fire incompatibilities	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
------------------------	--

Advice for firefighters

Fire Fighting	Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. *Caution: Use of water spray when fighting fire may be inefficient.
Fire/Explosion Hazard	HIGHLY FLAMMABLE LIQUID: Low flashpoint - Will be easily ignited by heat, sparks or flames at ambient temperatures Risk of violent reaction or explosion! Heating can cause expansion or decomposition leading to violent rupture of containers. Vapours will form explosive mixtures with air. Vapours will travel to source of ignition and flash back. Many vapours are heavier than air and will collect in low or confined areas. Vapours from the runoff may create an explosion hazard. Fire may produce irritating and/or toxic gases, including oxides of Carbon and Nitrogen, smoke and other toxic fumes.
HAZCHEM	•2Y

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	Remove all ignition sources. Avoid breathing vapours and contact with skin and eyes. Wipe up using paper towel or equivalent and dispose of safely.
Major Spills	Spill or leak area should be isolated immediately. Keep unauthorised personnel away. Keep upwind and to higher ground. No smoking, naked lights or ignition sources. Ensure adequate ventilation. All equipment used in handling the product must be earthed. Do not touch or walk through spilled material - Slippery when spilt. Avoid breathing vapours and contact with eyes. Absorb on sand, dirt, vermiculite or similar absorbent material. Place into labeled drums and dispose of according to local government regulations. Immediately notify emergency services (Police or Fire Brigade) if the spill is too large for you to safely and effectively handle.
PPE	Personal Protective Equipment advice is contained in Section 8 of the SDS

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Contains low boiling substance: Check for bulging containers. Vent periodically Always release caps or seals slowly to ensure slow dissipation of vapours.
Other information	Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. Store in a cool, dry, well-ventilated area out of direct sunlight. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities.

Suitable container	Keep in original container
Storage incompatibility	Avoid storing with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	ethanol, denatured	Ethyl alcohol	1880 mg/m3 / 1000 ppm	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
ethanol, denatured	Ethyl alcohol	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
ethanol, denatured	15.000 ppm	3,300[LLEL] ppm

Exposure controls

Appropriate engineering controls	Maintain adequate ventilation at all times. In most circumstances natural ventilation systems are adequate. If ventilation is poor, then the use of a local exhaust ventilation system is recommended.
Personal protection	 
Eye and face protection	Wear safety glasses with side shields or chemical goggles if splashing is likely.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves, e.g. PVC.
Body protection	See Other protection below
Other protection	Not usually necessary.
Thermal hazards	Not Available

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear liquid		
Physical state	Liquid	Relative density (Water = 1)	0.79 – 0.81
Odour	Characteristic alcohol	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature	Not Available
pH (as supplied)	7	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-114 - -117	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	13 - 18	Taste	Not Available
Evaporation rate	2.53 (n- Butyl Acetate = 1)	Explosive properties	Not Available
Flammability	Highly flammable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	100
Vapour pressure (Pa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Completely soluble	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	Risk of violent reaction or explosion
Conditions to avoid	Heat and sources of ignition
Incompatible materials	Incompatible/reactive with oxidising agents.acids and strong alkalis
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	Skin contact may cause irritation
Eye	Material may cause eye irritation
Chronic	No relevant data is available

Toxicological effects of ingredients

ethanol	Acute toxicity	Oral LD50 (mouse) 3450 mg/kg Inhalation LC50 (rat) 2000 ppm/10hrs
	Skin corrosion/irritation	Irritating to skin. Prolonged contact may result in drying and defatting of the skin, rash and dermatitis.
	Eye damage/irritation	Irritating to eyes. Exposure may result in lacrimation, irritation, pain and redness
	Respiratory/skin sensitization	No Data Available
	Germ cell mutagenicity	No Data Available
	Carcinogenicity	No Data Available
	Reproductive toxicity	No Data Available
	STOT (single exposure)	No Data Available
	STOT (repeated exposure)	Chronic ingestion may result in cirrhosis of the liver
	Aspiration toxicity	No Data Available

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

	Endpoint	Duration (Hr.)	Species	Value
ethanol	LC50	96	Fish	42-mg/L
	EC50	48	Crustacea	2-mg/L
	EC50	96	Algae or other aquatic plants	-8.358-26.503mg/L
	EC10	168	Algae or other aquatic plants	1.91-mg/L
	NOEC	2016	Fish	0.000375-mg/L

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
ethanol, denatured	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)

Bio accumulative potential

Ingredient	Bioaccumulation
ethanol, denatured	LOW (LogKOW = -0.31)

Mobility in soil

Ingredient	Mobility
ethanol, denatured	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of product/packaging	
	Containers may still present a chemical hazard/ danger when empty. Dispose of product / containers in accordance with local government regulations

SECTION 14 TRANSPORT INFORMATION

Labels Required

	
Marine Pollutant	NO
HAZCHEM	•2Y

Land transport (ADG):

UN Number	1170	
UN proper shipping name	ETHANOL (ETHYL ALCOHOL)	
Transport hazard class(es)	Class	3
	Sub risk	Not applicable
Packing group	II	
Environmental Hazard	Not applicable	
Special precautions for user	Special provisions	No data available
	Limited quantity	1L

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

ETHANOL, DENATURED IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australian Inventory of Industrial Chemicals (AIIC)

SECTION 16 OTHER INFORMATION

Revision Schedule

Revision Date	Not applicable
Initial Date	01/09/2025

SDS Version Summary

Version	Issue Date	Sections Updated
1.0	01/09/2025	All sections originated

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources such as the ECHA C&L Chemical Inventory, HSNO (CCID) New Zealand, AICIS and HCIS Australia

DISCLAIMER: While the information in this Safety Data Sheet (SDS) is believed to be true and accurate based on the current level of knowledge available to us, the author makes no representations as to its accuracy or sufficiency. Conditions of use are beyond the control of OMIKRON AUTO DETAILING PRODUCTS and therefore the users are responsible to verify this data under their own particular conditions of use, applications and regulations to determine whether the product is suitable for their particular purpose and they assume all risks of their use, handling, disposal, reliance upon, publication or use of the information contained herein. This information applies only to the product designated above and does not necessarily apply to its use in combination with other materials, products, chemical compounds, structures, or processes.

Definitions and abbreviations

PC-TWA;	Permissible Concentration-Time Weighted Average
PC-STEL;	Permissible Concentration-Short Term Exposure Limit
IARC:	International Agency for Research on Cancer
ACGIH;	American Conference of Government Industrial Hygienists
STEL:	Short Term Exposure Limit
TEEL:	Temporary Emergency Exposure Limit
IDLH:	Immediate Danger to Life or Health Concentrations
OSF:	Odour Safety Factor
NOAEL:	No Observed Effects Level
TLV:	Threshold Limit Value
LOD:	Limit Of Detection
OTV:	Odour Threshold Value
BCF:	Bio Concentration Factors
BEI:	Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from OMIKRON AUTO DETAILING PRODUCTS.

End of SDS